



* Rack KVM Drawers

Rack KVM Drawers

Features

- * TFT LCD, keyboard, touch-pad and KVM - 4 in 1
- * 3 layers daisy chain allowed for KVM
- * Plug&Play design, no additional software required
- * Auto Scan feature

- * Two level password protection
- * Special port protection – port lock
- * PS/2 keyboard and mouse emulation for smooth boot
- * TFT-LCD display with resolution up to 1280x1024
- * 250cd/m brightness, 350:1 contrast

Specifications

Model Name	AS-K1501	AS-K1508PS-D	AS-K1516DB-D	AS-K1708PS-D	AS-K1716DB-D
Connection					
KVM ports	1	8	16	8	16
Max controlled computers	-	512	4096	512	4096
Interface					
Computer Connection	Keyboard, Mouse	PS/2	HDB-15 Female	PS/2	HDB-15 Female
	Monitor	HDB-15 male	(combo)	HDB-15 male	(combo)
Console Connection	Keyboard, Mouse	-	PS/2	PS/2	PS/2
	Monitor	-	HDB-15 Female	HDB-15 Female	HDB-15 Female
Cable Type	-	PS/2 KVM Cable	3-in-1 Cable	PS/2 KVM Cable	3-in-1 Cable
Applicable to	PS/2 PC, Sun+, Mac	PS/2 PC, Sun+, Mac	PS/2 PC, Sun+, Mac	PS/2 PC, Sun+, Mac	PS/2 PC, Sun+, Mac
Monitoring and Control					
Port Selection	-	Hot Key; Button; OSD	Hot Key; Button; OSD	Hot Key; Button; OSD	Hot Key; Button; OSD
LEDs	-	8 (Red) 8 (Blue)	16 (Red) 16 (Blue)	8 (Red) 8 (Blue)	16 (Red) 16 (Blue)
Automatic Scan Interval	-	3-255 seconds	3-255 seconds	3-255 seconds	3-255 seconds
Physical and electrical characteristics					
Video Resolution	1024×768; 15" LCD	1024×768; 15" LCD	1024×768; 15" LCD	1280×1024; 17" LCD	1280×1024; 17" LCD
Power Consumption	120V, 60Hz, 24W 230V, 50Hz, 24W	120V, 60Hz, 24W 230V, 50Hz, 24W	120V, 60Hz, 24W 230V, 50Hz, 24W	120V, 60Hz, 24W 230V, 50Hz, 24W	120V, 60Hz, 24W 230V, 50Hz, 24W
Rear-mount Brackets	1U-height, Included	1U-height, Included	1U-height, Included	1U-height, Included	1U-height, Included
Housing	Metal	Metal	Metal	Metal	Metal
Humidity	0-80%RH	0-80%RH	0-80%RH	0-80%RH	0-80%RH
Dimensions LxWxH (mm)	114×404×40 (1U)	114×404×40 (1U)	114×404×40 (1U)	114×404×40 (1U)	114×404×40 (1U)

* Input plug and output sockets are optional.



* KVM Switch Extender AS-KEXT180

KVM Switch Extender AS-KEXT180

Features

- * Delivers the signal between two KVM devices located up to 180m apart one from the other
- * Image fine-tune function
- * VGA, SVGA, & Multi-sync monitors are supported
- * Supports monitor Display Data Channel (DDC)
- * Hot Key function available

- * LED control (PC, Link, Console Select)
- * VGA resolution 125MHz at 150m
- * CAT5 cable type
- * Small size: L×W×H - 132×79×32mm
- * 9V / 1000mA AC adapter power supply